


M12 male 90° / M12 female 90° Cube 67 PUR-OB 2x0,5 grey 0,3m

Cube67, 6-pole
Actuator supply external
Male 90° to female 90°
M12 - M12
2-pole used

Image



Vicarious picture

Approvals



Bus technologies

Form

46021

Technical Data

| | |
|---------------------------------------|---|
| Protection | IP65 and IP67 when plugged and screwed down (EN 60529) |
| Operating voltage | max. 125 V AC/DC |
| Operating current per contact (40 °C) | max. 4 A |
| Locking of ports | screw thread M12 × 1 mm (recommended torque = 0.6 Nm) self-securing |
| Temperature range | -25...+85 °C, depending on cable quality |

All data on this data sheet was compiled carefully.

Liability regarding correctness, completeness, and actuality is limited to gross negligence. Created: 06/12

| Cable | |
|----------------------------|-------------------------|
| No./diameter of wires | 2 × 0.5 mm ² |
| Wire isolation | PP (br, bl) |
| C-track properties | yes |
| Jacket | PUR |
| Outer diameter | approx. 4.4 mm |
| Bend radius (mobile) | 15 × outer diameter |
| Temperature range (fixed) | -40...+80 °C |
| Temperature range (mobile) | -20...+80 °C |

| Commercial data | |
|------------------------|----------|
| Net weight | 35 |
| Net weight | 35 |
| Weight unit | gram |
| Basic unit | pc. |
| Customs tariff number | 85444290 |
| Unit (piece) | 1 |
| Limited value | 1 |

Comments

Plastic housings with good resistance against chemicals and oils.
The resistance to aggressive media should be individually tested for your application. Further details on request.
Further cable lengths on request.

Representante oficial de:



[Argentina – Uruguay – Paraguay – Bolivia – Colombia – y Perú.]



Calle 49 N° 5764 - Villa Ballester (B1653AOX) - Prov. de Buenos Aires - ARGENTINA
Tel: (+54 11) 4768-4242 / Fax: (+54 11) 4849-1212
Mail: ventas@nakase.com.ar / Web: www.nakase.com.ar

