

M12 male / M12 female straight shielded Cube67 PUR-OB 4x0,5+2x0,25 shielded green 0,15m

Cube67, 6-pole
Hybrid cable for communication and supply
Male straight to female straight
M12 - M12
6-pole used, shielded

Image

Vicarious picture

Approvals**Bus technologies****Form**

46041

Technical Data

Operating voltage	max. 30 V AC/DC
Operating current per contact (40 °C)	max. 4 A
Locking of ports	screw thread M12 × 1 mm (recommended torque = 0.6 Nm) self-securing
Protection	IP65 and IP67 when plugged and screwed down (EN 60529)
Temperature range	-25...+85 °C, depending on cable quality

All data on this data sheet was compiled carefully.

Liability regarding correctness, completeness, and actuality is limited to gross negligence. Created: 06/12

Cable

No./diameter of wires	4 × 0.5 + 2 × 0.25 mm ²
Wire isolation	TPE (br, bl, bk, wh), (gr, pk)
C-track properties	5 Mio.
Jacket	PUR (UL/CSA)
Outer diameter	approx. 7.9 mm
Bend radius (mobile)	10 x outer diameter
Temperature range (fixed)	-50...+90 °C
Temperature range (mobile)	-40...+90 °C

Commercial data

Net weight	31
Net weight	31
Weight unit	gram
Basic unit	pc.
Customs tariff number	85444290
Unit (piece)	1
Limited value	1

Comments

Plastic housings with good resistance against chemicals and oils.
The resistance to aggressive media should be individually tested for your application. Further details on request.
Further cable lengths on request.

Representante oficial de:



[Argentina – Uruguay – Paraguay – Bolivia – Colombia – y Perú.]



Calle 49 N° 5764 - Villa Ballester (B1653AOX) - Prov. de Buenos Aires - ARGENTINA
Tel: (+54 11) 4768-4242 / Fax: (+54 11) 4849-1212
Mail: ventas@nakase.com.ar / Web: www.nakase.com.ar

