

**DESINA Hybrid field bus cable Cu-Cu-cable 2x0,34+4x1,5 violet 2m**

Male straight to female straight  
 DESINA® ECOFAST®  
 Connection cables Han-Brid®  
 6-pole, CU, shielded

**Image**

Vicarious picture

<b>Form</b>	33011
<b>Technical Data</b>	
Operating voltage	24 V AC/DC
Operating current per contact (40 °C)	max. 10 A
Protection	IP65 and IP67 when plugged and screwed down (EN 60529)
Locking of ports	Clip locking
Temperature range	-25...+85 °C, depending on cable quality
<b>Cable</b>	
No./diameter of wires	4 × 1.5 + 2 × 0.34 mm <sup>2</sup>
Wire isolation	PVC (bk, numbered),(rd, gn)
C-track properties	yes
Jacket	PUR
Outer diameter	approx. 10.0 mm
Bend radius (mobile)	8 × outer diameter
Temperature range (fixed)	-30...+70 °C
Temperature range (mobile)	-5...+80 °C
<b>Commercial data</b>	
Net weight	334
Net weight	334
Weight unit	gram
Basic unit	pc.
Customs tariff number	85444290
Unit (piece)	1
Limited value	1
<b>Accessories</b>	<b>Art.-No.</b>
DESINA Termination connector Replaced Art.-No. 67585	7000-33021-0000000

All data on this data sheet was compiled carefully.

Liability regarding correctness, completeness, and actuality is limited to gross negligence. Created: 06/12

**Comments**

Further cable lengths on request.

Han-Brid<sup>®</sup> a registered trademark of HARTING KGaA.

Plastic housings with good resistance against chemicals and oils.

The resistance to aggressive media should be individually tested for your application. Further details on request.