

M12 adaptor on top of MSUD valve form A 18mm Replaced Art.-No. 13852

Form A (18 mm) ? M12, connector top entry
without components
3-pole

Image

Vicarious picture

Approvals**Form**

41261

Technical Data

Operating voltage	125 V AC/DC
Operating current per contact (40 °C)	max. 4 A
Configuration	2 contacts + bridged PE
Switch off spike	<= 55 V
Current consumption	max. 15 mA
Protection	IP65 and IP67 when plugged and screwed down (EN 60529)
Temperature range	-25...+85 °C
Dimensions H x W x D	38 x 27 x 36 mm

Commercial data


Net weight	30
Net weight	30
Weight unit	gram
Basic unit	pc.
Customs tariff number	85369010
Unit (piece)	1
Limited value	1

Comments


Plastic housings with good resistance against chemicals and oils.
The resistance to aggressive media should be individually tested for your application. Further details on request.

All data on this data sheet was compiled carefully.
Liability regarding correctness, completeness, and actuality is limited to gross negligence. Created: 06/12

Contact layout



Circuit diagram



Representante oficial de:



[Argentina – Uruguay – Paraguay – Bolivia – Colombia – y Perú.]



Calle 49 N° 5764 - Villa Ballester (B1653AOX) - Prov. de Buenos Aires - ARGENTINA
Tel: (+54 11) 4768-4242 / Fax: (+54 11) 4849-1212
Mail: ventas@nakase.com.ar / Web: www.nakase.com.ar

