

**MSUD double valve form BI 11mm with cable PVC-JZ 4x0,75 yellow 1,5m**

Form BI (11 mm) industrial standard  
LED and suppression  
Connection cable L = 150 mm

**Image**

Vicarious picture

**Approvals****Form**

58121

**Technical Data**

Operating voltage	24 V AC/DC
Operating current per contact (40 °C)	max. 4 A
Switch off spike	<= 55 V
Switch off delay time	<= 20 ms
LED display	(yellow)
Current consumption	approx. 12 mA
Housing	Plastic, black (gray on request)
Temperature range	-25...+85 °C, depending on cable quality

**Cable**

No./diameter of wires	4 x 0.75 mm <sup>2</sup>
Wire isolation	PVC (bk, num, gnye)
C-track properties	Max. Externe Vorsicherung 20 A (T) in der Gebäudeinstallation
Jacket	PVC
Outer diameter	approx. 6.2 mm
Bend radius (mobile)	10 x outer diameter
Temperature range (fixed)	-30...+70 °C
Temperature range (mobile)	-5...+70 °C

All data on this data sheet was compiled carefully.

Liability regarding correctness, completeness, and actuality is limited to gross negligence. Created: 06/12

**Commercial data**

Net weight	170
Net weight	170
Weight unit	gram
Basic unit	pc.
Customs tariff number	85444290
Unit (piece)	1
Limited value	1

**Comments**

Further cable lengths on request.

Plastic housings with good resistance against chemicals and oils.

The resistance to aggressive media should be individually tested for your application. Further details on request.

Contact layout

