

**RC BUG2/24-48V AC/DC**

24 V AC/DC

48 V AC/DC

RC

**Image**

Vicarious picture

**Approvals****Appropriate contactors**

universal

DIL 6 (A) M, 6 H, DIL 8 (A) M, 8 H, 10 M, 10 H

**Technical Data**

Damping factor approx. 1.5 × UN

Temperature range -20...+70 °C

Material Flame retardant plastic acc. to (UL 94)

Connection wires self-securing cable forks

Hold-on 146 W(VA)

**Commercial data**

Net weight 105

Net weight 105

Weight unit gram

Basic unit pc.

Customs tariff number 85363010

Unit (piece) 1

Limited value 1


**Comments**

For other configurations and voltages, please inquire

All data on this data sheet was compiled carefully.

Liability regarding correctness, completeness, and actuality is limited to gross negligence. Created: 06/12

Circuit diagram



RC

Representante oficial de:



[Argentina – Uruguay – Paraguay – Bolivia – Colombia – y Perú.]



Calle 49 N° 5764 - Villa Ballester (B1653AOX) - Prov. de Buenos Aires - ARGENTINA  
Tel: (+54 11) 4768-4242 / Fax: (+54 11) 4849-1212  
Mail: [ventas@nakase.com.ar](mailto:ventas@nakase.com.ar) / Web: [www.nakase.com.ar](http://www.nakase.com.ar)

