

MIRO 6,2 pluggable plug in module output relay IN: 24 VDC - OUT: 250 VAC/DC / 6 A

1 C/O contact
24 V AC/DC
plug-in relay for base sockets

Image


- for MIRO 6.2 pluggable

Vicarious picture

Switching capacity according to (EN 60947)

| | | | |
|-------|----------|-----------|-------------|
| 24 V | AC12;6 A | AC15; 3 A | DC13; 1 A |
| 110 V | AC12;6 A | AC15; 3 A | DC13; 0.2 A |
| 230 V | AC12;6 A | AC15; 3 A | DC13; 0.1 A |

Technical Data

| | |
|---------------------------------------|--------------------|
| Switching voltage | max. 250 V AC/DC |
| Switching current | max. 6 A |
| Breaking capacity (voltage dependent) | max. 1500 VA/120 W |
| Min. load current | 10 mA/12 V DC |
| Contact material | Ag Sn O2 |
| Hold-on | 1.6 VA/0.65 W |
| Switching time | 8/4 ms |
| Dimensions H x W x D | 15 x 28 x 5 mm |

Commercial data

| | |
|-----------------------|----------|
| Net weight | 5 |
| Net weight | 5 |
| Weight unit | gram |
| Basic unit | pc. |
| Customs tariff number | 85364900 |
| Unit (piece) | 1 |
| Limited value | 1 |

Representante oficial de:



[Argentina – Uruguay – Paraguay – Bolivia – Colombia – y Perú.]



Calle 49 N° 5764 - Villa Ballester (B1653AOX) - Prov. de Buenos Aires - ARGENTINA
Tel: (+54 11) 4768-4242 / Fax: (+54 11) 4849-1212
Mail: ventas@nakase.com.ar / Web: www.nakase.com.ar

